

Vibro-Cast Crucible Size List

Model	Outer Diameter/mm	Inner Diameter/mm	Outer Height/mm	Inner Height/mm	Profile	Steel Capacity/kg
CC52	190	168	406	380	F	55
CC63	218	183	400	379	F	63
CC75	230	206	375	356	Rd	77
CC85	230	210	425	405	Rd	86
CC96	265	230	380	360	F	97
CC90	320	289	250	230	F	93
CC105	270	230	420	395	F	102
CC120	270	220	505	465	F	115
CC130	300	245	460	415	F	127
CC140	300	250	500	450	F	143
CC170	320	280	465	430	F, P	172
CC185	340	290	470	440	F	188
CC190	320	280	515	480	F	192
CC220	320	285	570	537	F	220
CC280	370	310	620	580	F, P	284
CC290	385	330	565	530	F	294
CC325	390	330	625	590	F	327
CC370	430	360	590	550	F	373
CC390	430	365	620	580	F, P	393
CC300	300	260	950	900	F, P	310
CC420	430	370	650	610	F, P	425
CC430	430	360	700	660	F	435
CC500	470	390	720	670	F, P	519
CC600	470	390	765	592	F, P	592
CC950	600	500	825	760	F	970
CC1000	600	500	875	810	F, P	1030
CC1050	600	500	915	850	F	1080
CC1100	600	505	915	850	F, P	1100
CC1125	600	500	955	895	F	1140
CC2000	705	605	1188	1125	F	2100

Steel capacity at 90% full, density 7.2g/cc. F=flat base Rd=rounded base P=pouring lip recess
 Many more sizes available; please ask. Lengths can be easily reduced by tooling modifications.